

Driver & Event	
Name	Maizer
Date	8/12/19
Event	Schumacher USGP
Weather	Outdoor dry 80 deg
Result	3rd

Track Conditions	
Grip Level	High <input checked="" type="checkbox"/> Med <input type="checkbox"/> Low <input type="checkbox"/>
Type	Tight <input type="checkbox"/> Open <input type="checkbox"/> Mixed <input checked="" type="checkbox"/>
Surface	Clay <input type="checkbox"/> Astro <input checked="" type="checkbox"/> Grass <input type="checkbox"/> Mixed <input type="checkbox"/> Carpet <input type="checkbox"/>
Condition	Smooth <input checked="" type="checkbox"/> Bumpy <input type="checkbox"/>

Differential	
Diff Oil F.	10k.....cSt
Diff Oil R.	7k.....cSt
Diff Height F	High <input type="checkbox"/> Mid <input type="checkbox"/> Low <input checked="" type="checkbox"/>
Diff Height R	High <input checked="" type="checkbox"/> Mid <input type="checkbox"/> Low <input type="checkbox"/>

Electrics & Chassis	
E.S.C	XR10PRO
Servo	Pro tech. 160t
Reciever	Sanwa
Lipo	5600hv
Shorty LiPo	Front <input checked="" type="checkbox"/> Middle <input type="checkbox"/> Rear <input type="checkbox"/>
Centre Topdeck	Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>
Front Topdeck Thickness	2.5mm <input checked="" type="checkbox"/> 3.0mm <input type="checkbox"/>
Rear Topdeck Thickness	2.5mm <input checked="" type="checkbox"/> 3.0mm <input type="checkbox"/>

Wheels & Tyres	
Rr Tyre	Darts yellow
Rr Wheel	Schumacher
Rr Insert	Schumacher
Fr Tyre	Dart yellow
Fr Wheel	Schumacher
Fr Insert	Schumacher

Motor & Gearing	
Motor	5.5 lrp
Rotor Diameter	12.5 mm
Timing	24 Deg
Spur	83
Pinion	19

Other settings	
Car Weight ?	9 g
Alloy Wing Mount	High <input type="checkbox"/> Low <input type="checkbox"/>
Rear Wing Gurney Height	6 mm
Front Wing	Small <input type="checkbox"/> Big <input type="checkbox"/>
Front Wing Gurney Height	15mm mm
Slipper	2Plate <input checked="" type="checkbox"/> 3Plate <input type="checkbox"/> 4Plate <input type="checkbox"/>
Rear Hex	0 <input type="checkbox"/> 0.75 <input type="checkbox"/> 1.5 <input checked="" type="checkbox"/>
Front Hex	0 <input type="checkbox"/> 0.75 <input type="checkbox"/> 1.5 <input checked="" type="checkbox"/>

Front Shocks	
Oil	42.5w.....cSt
Spring	Yellow.....lb/in
Shock Cap	Sealed <input type="checkbox"/> Aeration <input checked="" type="checkbox"/>
Piston	2.hole..... Drilled <input type="checkbox"/>
Hole Size	1.6.....mm
Internal Limiters	0.....mm
Kashima Body	No <input type="checkbox"/> Yes <input checked="" type="checkbox"/>

Rear Shocks	
Oil	32.5w.....cSt
Spring	Blue.....lb/in
Shock Cap	Sealed <input type="checkbox"/> Aeration <input checked="" type="checkbox"/>
Piston	3.hole..... Drilled <input type="checkbox"/>
Hole Size	1.6.....mm
Internal Limiters	0.....mm
Kashima Body	No <input type="checkbox"/> Yes <input checked="" type="checkbox"/>
Shock Stand Off Spacing	.....mm

Front Suspension	
Toe	0.....Deg
Yoke	8° <input checked="" type="checkbox"/> 10° <input type="checkbox"/> 12° <input type="checkbox"/>
Anti Roll Bar	None <input type="checkbox"/> 1.2 <input type="checkbox"/> 1.4 <input type="checkbox"/> 1.6 <input checked="" type="checkbox"/> 1.8 <input type="checkbox"/> 2.0 <input type="checkbox"/>
Ride Height	16.....mm
Camber at Ride Height	14.....Deg
Link Washers	3.....mm
Wheelbase	Short <input type="checkbox"/> Long <input checked="" type="checkbox"/>
Shock Mount	C/F <input type="checkbox"/> S2 <input checked="" type="checkbox"/>
Bump Steer Washers	0.....mm
Hub Spacer	High <input type="checkbox"/> Low <input checked="" type="checkbox"/>
Driveshaft	Kit <input type="checkbox"/> Roche <input checked="" type="checkbox"/>
Pin Angle	8° <input type="checkbox"/> 10° <input type="checkbox"/> 12° <input checked="" type="checkbox"/>
Pin Width	Narrow <input type="checkbox"/> Mid <input checked="" type="checkbox"/> Wide <input type="checkbox"/>

Rear Suspension	
Toe In (Kit Blocks)	3° <input type="checkbox"/> 2.5° <input checked="" type="checkbox"/>
Toe In (3.5/1.2° Blocks)	3.5° <input type="checkbox"/> 2° <input checked="" type="checkbox"/>
Toe In (4°/1.5° Blocks)	4° <input type="checkbox"/> 1.5° <input checked="" type="checkbox"/>
Anti-squat	1° <input type="checkbox"/> 2° <input type="checkbox"/> 3° <input checked="" type="checkbox"/> 4° <input type="checkbox"/>
Anti Roll Bar	None <input type="checkbox"/> 1.2 <input type="checkbox"/> 1.4 <input type="checkbox"/> 1.6 <input checked="" type="checkbox"/> 1.8 <input type="checkbox"/> 2.0 <input type="checkbox"/>
Ride Height	16.....mm
Camber at Ride Height	1.....Deg
Wheelbase	Short <input type="checkbox"/> Med <input checked="" type="checkbox"/> Long <input type="checkbox"/>
Shock Mount	C/F <input type="checkbox"/> S2 <input checked="" type="checkbox"/>
Wing Mount	Alloy <input type="checkbox"/> Kit <input checked="" type="checkbox"/>
Wing Washer	No <input type="checkbox"/> Yes <input checked="" type="checkbox"/>
Hub Washers	.....mm
Link Washers	1.....mm
Rear Strap	High Pin (With front Riser) <input type="checkbox"/> Low Pin (Kit) <input checked="" type="checkbox"/>
Hub Carrier	Kit <input type="checkbox"/> Alloy <input checked="" type="checkbox"/>
Brass insert	Hi-Pin <input type="checkbox"/> Low-Pin <input checked="" type="checkbox"/>
Link Mount	Kit <input type="checkbox"/> Alloy <input checked="" type="checkbox"/>

**Notes**

2.25 rear hexes , cut front dart pins two outside rows one inside row glue outside sidewall.