

DRIVER AND EVENT DETAILS

Name *Martin Hofer*
 Date *11-02-11 - 13-02-11*
 Event *ETS Rd3 Austria*
 Weather
 Result *TQ and Win!*

CHASSIS AND ELECTRICS

Chassis *2mm*
 Top Deck *2mm*
 Bodyshell *Speed 6 LW*
 Wing *10mm overhang a.p. efra rules*
 E.S.C *SP*
 Servo *Sanwa 801*
 Receiver *Sanwa 451*
 Cells *GM 50C*

TRACK CONDITIONS

Grip Level High Medium Low
 Type Tight Open Both
 Surface Carpet Tarmac Wood
 Condition Smooth Bumpy
 Temperature *15* °C °F
 Venue Indoor Outdoor



WHEELS, TYRES AND INSERTS

Wheels *TOP spoke wheel*
 Tyres *TOP Solaris M*
 Inserts
 Tyre Additive *Marc Rheinard*
 Additive Time *25 MIN (R) 25 MIN (F)*
 Tyre Warmers Yes No

DRIVER NOTES

double post steering


Front Shocks

Oil *45 WT*
 Springs *HPI pink*
 Piston Holes *2* *3*
 length *12.7*
 Rebound *20%*




FRONT SETTINGS

Drive Diff Spool One-Way Height High Low

Servo Saver Yes No Yoke Flex X M STD
 Pivot Blocks Moulded (std) Alloy
 Screw Block Spacers Front *2.5 mm* Rear *2.5 mm*
 Wishbone Quik-Klips Front *2.5 mm* Rear *1.5 mm*
 Toe In-Out In-board Out-board *0.3* °
 Ride Height (Chassis to Floor) *4.0 mm*
 Droop On 10mm Block Axle Height *6.0 mm*
 Anti-roll Bar No *1.20* *1.40* *1.60*
 Castor *0*° *2*° *4*° *6*°
 Camber Positive Negative *1.5 Deg*
 Link Washers Under Ball Under Bracket *2 mm*
 Inboard Pin Kick-up Anti-dive Horizontal
 Pivot Block Spacers Front *1.5 mm* Rear *1.5 mm*



Wishbone Flex CF M



Centre Track Rod

Washers *mm*


Link Mount

1 Groove - 45mm
 2 Groove - 42mm
 3 Groove - 39mm
 4 Groove - 37mm


REAR SETTINGS

Drive Height High Low

Pivot Blocks Moulded (std) Alloy
 Screw Block Spacers Front *2 mm* Rear *0.5 mm*
 Wishbone Quik-Klips Front *2 mm* Rear *2 mm*
 Toe In In-board *2.5*° Out-board °
 Ride Height (Chassis to Floor) *4.2 mm*
 Droop On 10mm Block Axle Height *5.2 mm*
 Anti-roll Bar No *1.20* *1.40* *1.60*
 Camber Positive Negative *2 Deg*
 Link Washers Under Ball Under Bracket *1.5 mm*
 Inboard Pin Pro-Squat Anti-Squat Horizontal
 Pivot Block Spacers Front *2.5 mm* Rear *mm*





Wishbone Flex CF M



Link Mount

1 Groove - 45mm
 2 Groove - 42mm
 3 Groove - 39mm
 4 Groove - 37mm



Rear Shocks

Oil *45 WT*
 Springs *HPI silver*
 Piston Holes *2* *3*
 length *12,7*
 Rebound *20%*