

DRIVER AND EVENT DETAILS

Name Chris Grainger
 Date October 2010
 Event Ardent Test
 Weather _____
 Result _____

CHASSIS AND ELECTRICS

Chassis Standard 2mm
 Top Deck Standard 2.5mm
 Bodyshell PF Speed 6
 Wing Standard
 E.S.C GM120
 Servo KO
 Receiver KO
 Cells GM 500 lipo

TRACK CONDITIONS

Grip Level High Medium Low
 Type Tight Open Both
 Surface Carpet Tarmac Wood
 Condition Smooth Bumpy
 Temperature 20 °C °F
 Venue Indoor Outdoor

**MOTOR AND GEARING**

Motor GM 8t
 Rotor Diameter 12.5
 Timing Standard
 Gear Pitch 48Dp 64Dp
 Spur Size 89
 Pinion Size 23

Transmission

Option 1 Option 2

WHEELS, TYRES AND INSERTS

Wheels Schumacher
 Tyres Sorex 28R
 Inserts JB
 Tyre Additive Nosram Carpet
 Additive Time 20MIN (R) 10MIN (F)
 Tyre Warmers Yes No

DRIVER NOTES

Narrow front hex.


Front Shocks

Oil 50 WT
 Springs HPI Pink
 Piston Holes 2 3
 length 12.8
 Rebound 0 %




FRONT SETTINGS

Drive Diff Spool One-Way Height High Low

Servo Saver Yes No Yoke Flex X M STD
 Pivot Blocks Moulded (std) Alloy
 Screw Block Spacers Front 2 mm Rear 2 mm
 Wishbone Quik-Klips Front 2 mm Rear 2 mm
 Toe In-Out In-board Out-board 1°
 Ride Height (Chassis to Floor) 5 mm
 Droop On 10mm Block Axle Height 5.5 mm
 Anti-roll Bar No 1.20 1.40 1.60
 Castor 0° 2° 4° 6°
 Camber Positive Negative 2 Deg
 Link Washers Under Ball Under Bracket 1 mm
 Inboard Pin Kick-up Anti-dive Horizontal
 Pivot Block Spacers Front mm Rear mm



Wishbone Flex CF M

**Centre Track Rod**

Washers 4 mm


Link Mount

1 Groove - 45mm
 2 Groove - 42mm
 3 Groove - 39mm
 4 Groove - 37mm


REAR SETTINGS

Drive Height High Low



Pivot Blocks Moulded (std) Alloy
 Screw Block Spacers Front 1 mm Rear 1 mm
 Wishbone Quik-Klips Front 2 mm Rear 2 mm
 Toe In In-board 3° Out-board °
 Ride Height (Chassis to Floor) 5.5 mm
 Droop On 10mm Block Axle Height 5 mm
 Anti-roll Bar No 1.20 1.40 1.60
 Camber Positive Negative Deg
 Link Washers Under Ball Under Bracket 0 mm
 Inboard Pin Pro-Squat Anti-Squat Horizontal
 Pivot Block Spacers Front mm Rear mm



Wishbone Flex CF M

**Link Mount**

1 Groove - 45mm
 2 Groove - 42mm
 3 Groove - 39mm
 4 Groove - 37mm

**Rear Shocks**

Oil 50 WT
 Springs HPI Silver
 Piston Holes 2 3
 length 12.8
 Rebound 0 %