

DRIVER AND EVENT DETAILS

Name Chris Grainger
 Date Summer 2009
 Event Cotswolds Test
 Weather Fine
 Result

CHASSIS AND ELECTRICS

Chassis Standard 2mm
 Top Deck Standard 2mm
 Bodyshell PF LTC
 Wing Standard
 E.S.C GM120
 Servo KO
 Receiver KO
 Cells GM

TRACK CONDITIONS

Grip Level High Medium Low
 Type Tight Open Both
 Surface Carpet Tarmac Wood
 Condition Smooth Bumpy
 Temperature 20 °C °F
 Venue Indoor Outdoor

Mi4cx

MOTOR AND GEARING

Motor GM 4.5t
 Rotor Diameter 12.5
 Timing
 Gear Pitch 48Dp 64Dp
 Spur Size 89
 Pinion Size 21

Transmission

Option 1 Option 2

WHEELS, TYRES AND INSERTS

Wheels
 Tyres Sorex XG32RY Pre-Glued
 Inserts
 Tyre Additive MR
 Additive Time 30MIN (R) 30MIN (F)
 Tyre Warmers Yes No

DRIVER NOTES

Narrow front hex.
 Alloy shock spring retainers.


Front Shocks

Oil 40 WT
 Springs Hara Black
 Piston Holes 2 3
 length 12.6
 Rebound 100%




FRONT SETTINGS

Drive Diff Spool One-Way Height High Low

Servo Saver Yes No Yoke Flex X M STD
 Pivot Blocks Moulded (std) Alloy
 Screw Block Spacers Front 2.5 mm Rear 2.5 mm
 Wishbone Quik-Klips Front 2.5 mm Rear 1.5 mm
 Toe In-Out In-board Out-board 1°
 Ride Height (Chassis to Floor) 5 mm
 Droop On 10mm Block Axle Height 5 mm
 Anti-roll Bar No 1.20 1.40 1.60
 Castor 0° 2° 4° 6°
 Camber Positive Negative 2 Deg
 Link Washers Under Ball Under Bracket 1.5 mm
 Inboard Pin Kick-up Anti-dive Horizontal
 Pivot Block Spacers Front mm Rear mm



Wishbone Flex CF M



Centre Track Rod

Washers 3 mm


Link Mount

1 Groove - 45mm
 2 Groove - 42mm
 3 Groove - 39mm
 4 Groove - 37mm


REAR SETTINGS

Drive Height High Low

Pivot Blocks Moulded (std) Alloy
 Screw Block Spacers Front 1 mm Rear 1 mm
 Wishbone Quik-Klips Front 2 mm Rear 2 mm
 Toe In In-board 3° Out-board 0°
 Ride Height (Chassis to Floor) 5.5 mm
 Droop On 10mm Block Axle Height 4 mm
 Anti-roll Bar No 1.20 1.40 1.60
 Camber Positive Negative 2 Deg
 Link Washers Under Ball Under Bracket 0 mm
 Inboard Pin Pro-Squat Anti-Squat Horizontal
 Pivot Block Spacers Front mm Rear mm




Wishbone Flex CF M



Link Mount

1 Groove - 45mm
 2 Groove - 42mm
 3 Groove - 39mm
 4 Groove - 37mm



Rear Shocks

Oil 40 WT
 Springs Hara Black
 Piston Holes 2 3
 length 12.6
 Rebound 100%