

## DRIVER AND EVENT DETAILS

Name Test Driver  
 Date 2010  
 Event Test  
 Weather \_\_\_\_\_  
 Result \_\_\_\_\_

## CHASSIS AND ELECTRICS

Chassis Standard 2mm  
 Top Deck Standard 2mm  
 Bodyshell East Coast Speed 6  
 Wing Standard  
 E.S.C GM120  
 Servo KO  
 Receiver KO  
 Cells GM 500 lipo

## TRACK CONDITIONS

Grip Level High  Medium  Low   
 Type Tight  Open  Both   
 Surface Carpet  Tarmac  Wood   
 Condition Smooth  Bumpy   
 Temperature 15 °C °F \_\_\_\_\_  
 Venue Indoor  Outdoor

# Mi4cx

## MOTOR AND GEARING

Motor GM 10.5t  
 Rotor Diameter Standard  
 Timing Standard  
 Gear Pitch 48Dp  64Dp   
 Spur Size \_\_\_\_\_  
 Pinion Size \_\_\_\_\_

## Transmission

Option 1  Option 2

## WHEELS, TYRES AND INSERTS

Wheels Schumacher  
 Tyres \_\_\_\_\_  
 Inserts \_\_\_\_\_  
 Tyre Additive \_\_\_\_\_  
 Additive Time MIN (R) MIN (F)  
 Tyre Warmers Yes  No

## DRIVER NOTES

Low grip set up.


## Front Shocks

Oil 35 WT  
 Springs White  
 Piston Holes 2  3   
 length 12.6  
 Rebound 100%




## FRONT SETTINGS

Drive Diff  Spool  One-Way  Height High  Low

Servo Saver Yes  No  Yoke Flex X  M  STD   
 Pivot Blocks Moulded (std)  Alloy   
 Screw Block Spacers Front 1.5mm Rear 1.5mm  
 Wishbone Quik-Klips Front 2mm Rear 2mm  
 Toe In-Out In-board  Out-board  -1°  
 Ride Height (Chassis to Floor) 5 mm  
 Droop On 10mm Block  Axle Height  5 mm  
 Anti-roll Bar No  1.20  1.40  1.60   
 Castor 0°  2°  4°  6°   
 Camber Positive  Negative  2 Deg  
 Link Washers Under Ball  Under Bracket  0.5mm  
 Inboard Pin Kick-up  Anti-dive  Horizontal   
 Pivot Block Spacers Front mm Rear mm



Wishbone Flex CF  M



## Centre Track Rod

Washers 2mm


## Link Mount

1 Groove - 45mm   
 2 Groove - 42mm   
 3 Groove - 39mm   
 4 Groove - 37mm


## REAR SETTINGS

Drive Height High  Low

Pivot Blocks Moulded (std)  Alloy   
 Screw Block Spacers Front 2mm Rear 2mm  
 Wishbone Quik-Klips Front 2mm Rear 2mm  
 Toe In In-board  3° Out-board  0°  
 Ride Height (Chassis to Floor) 5.5 mm  
 Droop On 10mm Block  Axle Height  4 mm  
 Anti-roll Bar No  1.20  1.40  1.60   
 Camber Positive  Negative  2 Deg  
 Link Washers Under Ball  Under Bracket  1 mm  
 Inboard Pin Pro-Squat  Anti-Squat  Horizontal   
 Pivot Block Spacers Front mm Rear mm




Wishbone Flex CF  M



## Link Mount

1 Groove - 45mm   
 2 Groove - 42mm   
 3 Groove - 39mm   
 4 Groove - 37mm



## Rear Shocks

Oil 35 WT  
 Springs White  
 Piston Holes 2  3   
 length 12.6  
 Rebound 100%