

DRIVER AND EVENT DETAILS

Name
 Date
 Event
 Weather
 Result

CHASSIS AND ELECTRICS

Chassis
 Top Deck
 Bodyshell
 Wing
 E.S.C
 Servo
 Receiver
 Cells
 Cell Position Backward Forward

TRACK CONDITIONS

Grip Level High Medium Low
 Type Tight Open Both
 Surface Carpet Tarmac Wood
 Condition Smooth Bumpy
 Temperature 14 °C °F
 Venue Indoor Outdoor



MOTOR AND GEARING

Motor
 Rotor Diameter
 Timing
 Gear Pitch 48Dp 64Dp
 Spur Size
 Pinion Size

Transmission

Option 1 Option 2

WHEELS, TYRES AND INSERTS

Wheels
 Tyres
 Inserts
 Tyre Additive CS
 Additive Time 30 MIN (R) 30 MIN (F)
 Tyre Warmers Yes No

DRIVER NOTES

narrow front hex, 0.5mm on rear hex, front sidewalls glued, doublejoint driveshafts

Front Shocks

Oil 35 WT
 Springs Tamiya White
 Piston Holes 2 3
 length 12.6
 Rebound 90 %

FRONT SETTINGS

Drive Diff Spool One-Way Height High Low

Servo Saver Yes No Yoke Flex X M STD

Pivot Blocks Moulded (std) Alloy

Screw Block Spacers Front 2.5 mm Rear 2.5 mm

Wishbone Quik-Klips Front 2.5 mm Rear 1.5 mm

Toe In-Out In-board Out-board 1.5 °

Ride Height (Chassis to Floor) 5.0 mm

Droop On 10mm Block Axle Height 5.0 mm

Anti-roll Bar No 1.20 1.40 1.60


Castor 0° 2° 4° 6°

Camber Positive Negative 1.5 Deg




Link Washers Under Ball Under Bracket 2.0mm

Inboard Pin Kick-up Anti-dive Horizontal

Pivot Block Spacers Front mm Rear mm



Wishbone Flex CF M



Centre Track Rod

Washers 1.5 mm

Link Mount

1 Groove - 45mm
 2 Groove - 42mm
 3 Groove - 39mm
 4 Groove - 37mm

REAR SETTINGS

Diff Ball Gear Oil "C" Height High Low

Pivot Blocks Moulded (std) Alloy

Screw Block Spacers Front 0.5 mm Rear 0.5 mm

Wishbone Quik-Klips Front 2.0mm Rear 2:0mm

Toe In In-board 3° Out-board °

Ride Height (Chassis to Floor) 5.2 mm

Droop On 10mm Block Axle Height 4.5 mm


Anti-roll Bar No 1.20 1.40 1.60

Camber Positive Negative 2.0 Deg


Link Washers Under Ball Under Bracket 0mm

Inboard Pin Pro-Squat Anti-Squat Horizontal

Pivot Block Spacers Front mm Rear mm



Wishbone Flex CF M




Link Mount

1 Groove - 45mm
 2 Groove - 42mm
 3 Groove - 39mm
 4 Groove - 37mm

Qwik Clips

Front .5 mm
 Rear .5 mm



Rear Shocks

Oil 42.5 WT
 Springs Tamiya Blue
 Piston Holes 2 3
 length 12.6
 Rebound 15 %