

DRIVER AND EVENT DETAILS

Name Martin Hofer
 Date 12-14.10.12
 Event ETS Rd.1
 Weather ?
 Result 4th

CHASSIS AND ELECTRICS

Chassis Stet 2in
 Top Deck tarmac
 Bodyshell Pf Speed 6 LW, 6mm Rev.
 Wing MR33, 17high, 10overhang
 E.S.C hondolent
 Servo GM HGM-SLP [SHR-mode]
 Receiver Sanwa 451R
 Cells GM 40C
 Cell Position Backward Forward

TRACK CONDITIONS

Grip Level High Medium Low
 Type Tight Open Both
 Surface Carpet Tarmac Wood
 Condition Smooth Bumpy
 Temperature 20 °C °F
 Venue Indoor Outdoor



MOTOR AND GEARING

Motor hondolent
 Rotor Diameter _____
 Timing _____
 Gear Pitch 48Dp 64Dp
 Spur Size 30
 Pinion Size 36
 Transmission
 Option 1 Option 2

WHEELS, TYRES AND INSERTS

Wheels Riole
 Tyres /
 Inserts /
 Tyre Additive CS High
 Additive Time 20 MIN (R) 20 MIN (F)
 Tyre Warmers Yes No

DRIVER NOTES

*narrow front hex, 0.5 against rear hex,
 1mm bumpsteer shim, T-Shox, Spec-R
 shafts, new suspension mounts,
 glued front
 sidewalls*


Front Shocks

Oil 400 Core WT
 Springs Yokomo Pink
 Piston Holes 2 3
 length 14.0
 Rebound short soft %



FRONT SETTINGS

Drive Diff Spool One-Way Height High Low

Servo Saver Yes No Yoke Flex X M STD
 Pivot Blocks Moulded (std) Alloy
 Screw Block Spacers Front 2.5 mm Rear 2.5 mm
 Wishbone Quik-Klips Front 2.7 mm Rear 1.5 mm
 Toe In-Out In-board Out-board 1.7 0.5°
 Ride Height (Chassis to Floor) 5.0 mm
 Droop On 10mm Block Axle Height 5.0 mm
 Anti-roll Bar No 1.20 1.40 1.60
 Castor 0° 2° 4° 6°
 Camber Positive Negative 1.5 Deg
 Link Washers Under Ball Under Bracket 2.0 mm
 Inboard Pin Kick-up Anti-dive Horizontal
 Pivot Block Spacers Front / mm Rear / mm



Wishbone Flex CF M



Centre Track Rod

Washers 2.0 mm


Link Mount

1 Groove - 45mm
 2 Groove - 42mm
 3 Groove - 39mm
 4 Groove - 37mm


REAR SETTINGS

Diff Ball Gear Oil 4000 Height High Low

Pivot Blocks Moulded (std) Alloy
 Screw Block Spacers Front 0.5 mm Rear 2.5 mm
 Wishbone Quik-Klips Front 2.2 mm Rear 2.0 mm
 Toe In In-board 3° Out-board °
 Ride Height (Chassis to Floor) 5.2 mm
 Droop On 10mm Block Axle Height 4.5 mm
 Anti-roll Bar No 1.20 1.40 1.60
 Camber Positive Negative 2.0 Deg
 Link Washers Under Ball Under Bracket 0 mm
 Inboard Pin Pro-Squat Anti-Squat Horizontal
 Pivot Block Spacers Front / mm Rear / mm



Wishbone Flex CF M




Link Mount

1 Groove - 45mm
 2 Groove - 42mm
 3 Groove - 39mm
 4 Groove - 37mm

Quik Clips

Front 0.6 mm
 Rear 0.5 mm



Rear Shocks

Oil 400 Core WT
 Springs Yokomo Blue
 Piston Holes 2 3
 length 12.0
 Rebound short soft %