

DRIVER AND EVENT DETAILS

Name Paul Pinkney
 Date 04/03/2012
 Event Sweep Rugracers Rd 6
 Weather
 Result TQ & Win

TRACK CONDITIONS

Grip Level High Medium Low
 Type Tight Open Both
 Surface Carpet Tarmac Wood
 Condition Smooth Bumpy
 Temperature 18 °C °F
 Venue Indoor Outdoor



CHASSIS AND ELECTRICS

Chassis 2mm Soft Weave
 Top Deck Carpet
 Bodyshell PF Mazda Speed 6 L/W
 Wing MR Wing
 E.S.C Speed Passion GT2.0Pro
 Servo Futaba 9551
 Receiver Sanwa 451r
 Cells Demon Shorty 4470
 Cell Position Backward Forward

MOTOR AND GEARING

Motor SP 13.5t mmm
 Rotor Diameter 12.3
 Timing std
 Gear Pitch 48Dp 64Dp
 Spur Size 114
 Pinion Size 28

Transmission

Option 1 Option 2

WHEELS, TYRES AND INSERTS

Wheels Sweep
 Tyres 30pp
 Inserts
 Tyre Additive Nosram Carpet
 Additive Time 10 MIN (R) 10 MIN (F)
 Tyre Warmers Yes No

DRIVER NOTES

Narrow Front Hex, 0.5 Against Rear Hex, 1mm Hole in shock cap.

Front Shocks

Oil 40 WT
 Springs Tamiya White
 Piston Holes 2 3
 length 12.7
 Rebound 0 %

FRONT SETTINGS

Drive Diff Spool One-Way Height High Low

Servo Saver Yes No Yoke Flex X M STD

Pivot Blocks Moulded (std) Alloy

Screw Block Spacers Front 2.5 mm Rear 2.5 mm

Wishbone Quik-Klips Front 2.5 mm Rear 1.5 mm

Toe In-Out In-board Out-board 0.3mm °

Ride Height (Chassis to Floor) 5.5 mm

Droop On 10mm Block Axle Height 5 mm

Anti-roll Bar No 1.20 1.40 1.60


Castor 0° 2° 4° 6°

Camber Positive Negative 1.5 Deg




Link Washers Under Ball Under Bracket 2mm

Inboard Pin Kick-up Anti-dive Horizontal

Pivot Block Spacers Front mm Rear mm



Wishbone Flex CF M



Centre Track Rod

Washers 1.5 mm

Link Mount

1 Groove - 45mm
 2 Groove - 42mm
 3 Groove - 39mm
 4 Groove - 37mm

REAR SETTINGS

Diff Ball Gear Oil 80 Height High Low

Pivot Blocks Moulded (std) Alloy

Screw Block Spacers Front 0.5 mm Rear 0.5 mm

Wishbone Quik-Klips Front 2mm Rear 2mm

Toe In In-board 3° Out-board °

Ride Height (Chassis to Floor) 5.8 mm

Droop On 10mm Block Axle Height 5.5 mm


Anti-roll Bar No 1.20 1.40 1.60

Camber Positive Negative 2 Deg


Link Washers Under Ball Under Bracket 1mm

Inboard Pin Pro-Squat Anti-Squat Horizontal

Pivot Block Spacers Front mm Rear 0mm



Wishbone Flex CF M




Link Mount

1 Groove - 45mm
 2 Groove - 42mm
 3 Groove - 39mm
 4 Groove - 37mm

Quik Clips

Front 0.5 mm
 Rear 0.5 mm



Rear Shocks

Oil 40 WT
 Springs Tamiya Blue
 Piston Holes 2 3
 length 12.7
 Rebound 0 %