

DRIVER DETAILS

NAME **Martin Hofer**
 DATE **Feb '14**
 EVENT **Carpet Test**
 WEATHER **N/A**
 RESULT **N/A**

NOTES



CHASSIS AND ELECTRICS

CHASSIS **Std** Rear Motor Mid Motor
 TOP DECK **Std**
 BODYSHELL **Mazda 6**
 WING **Schumacher**
 E.S.C **GM**
 SERVO **GM**
 RECIEVER **Sanwa**
 CELLS **GM**
 CELL POSITION Forward Rearward

MOTOR AND GEARING

MOTOR **5.5**
 ROTOR DIAMETER **Std**
 TIMING **Std**
 GEAR PITCH 48DP 64DP
 SPUR SIZE **114**
 PINION SIZE **23**

TRACK CONDITIONS

GRIP LEVEL High Medium Low
 TYPE Tight Open Mixed
 SURFACE Carpet Tarmac
 CONDITION Smooth Bumpy
 TEMPERATURE °C **20** °F
 VENUE Indoor Outdoor

WHEELS, TYRES AND INSERTS

WHEELS **Control**
 TYRES **Control**
 INSERTS **Control**
 TYRE ADDITIVE
 ADDITIVE TIME Front Minutes Rear Minutes
 TYRE WARMERS Yes No Temp °C Time Minutes

FRONT

Spool
 Gear Diff
 Diff Oil cTs

0 Dot - 1.0mm
 1 Dot - 1.1mm
 2 Dot - 1.2mm
 3 Dot - 1.3mm
 4 Dot - 1.4mm
 5 Dot - 1.5mm
 6 Dot - 1.6mm

Washers **1.0** mm
 Droop.....**5**.....mm
 On 10mm Block
 Ride Height.....**4.5**.....mm
 Camber.....**1.5**.....Degree's
 Toe-in..........Degree's
 Toe-out.....**1**.....Degree's

Washers **1.5** mm
 Washers **1.0** mm

Washers mm

4° R 4° Yoke
 6° Yoke
 SERVO SAVER Yes
 No

7075-T8
 Washers **1.0** mm

CAP TYPE Vented Sealed Emulsion
 OIL.....**500**.....cTs
 SPRING.....**Red**.....
 PISTON.....**Std**.....
 DRILLED Yes No
 DRILLED PISTON HOLE SIZE.....**1.1**.....mm
 SHOCK LENGTH (X).....**10.5**.....mm
 REBOUND.....**20**.....%

Alloy Steel Double Joint

X=.....**0**.....mm

REAR

Ball Diff
 Gear Diff
 Diff Oil **.3000** cTs

0 Dot - 1.0mm
 1 Dot - 1.1mm
 2 Dot - 1.2mm
 3 Dot - 1.3mm
 4 Dot - 1.4mm
 5 Dot - 1.5mm
 6 Dot - 1.6mm

Droop.....**4**.....mm
 On 10mm Block
 Ride Height.....**5.0**.....mm
 Camber.....**2**.....Degree's
 Washers **1.5** mm
 Washers **0.5** mm

(2 Pip shown)
 0 Pip 3.0°
 1 Pip 2.5°
 2 Pip 2.0°

Washers mm

(2 Pip shown)
 0 Groove
 1 Groove
 2 Groove
 Washers **1.0** mm
 WheelBase Short
 Middle
 Long
 CAP TYPE Vented Sealed Emulsion
 OIL.....**500**.....cTs
 SPRING.....**Green**.....
 PISTON.....**Std**.....
 DRILLED Yes No
 DRILLED PISTON HOLE SIZE.....**1.1**.....mm
 SHOCK LENGTH (X).....**10.5**.....mm
 REBOUND.....**20**.....%

Alloy Steel