

COUGAR SV2

| | | | | | |
|----------------------------------|---|---|--|--|-----------------------------------|
| Driver and Event | | Track Conditions | | Additional Settings | |
| Name Tom Cockerill | Date Dec '12 | Surface AstroTurf | Grip Level High | Weights Added | See Notes |
| Event Silverstone Winter Masters | Weather Indoors | Track Condition Smooth | Wooden Jumps | Cell Layout | Saddle Forward |
| Result TQ & 2nd | | | | Ride Height | Front 17 mm Rear 18 mm |
| Electrics and Gearing | | Wheels and Tyres | | Washers between CTR and Bellcranks 4.0 mm | |
| E.S.C Speed Passion | Servo GM | Rear Wheels Schumacher Flex | Rear Tyre Schumacher MiniSpike | NOTES 40g in Front of Motor, 20g in Nose, 15g Under Servo. Rear Piston Drilled to 1.65mm. SVR Front Arms | |
| Reciever KO | Batteries Speed Power 4200 | Rear Insert Schumacher Medium | Front Wheels Cut Med. Schumacher Flex | | |
| Motor Speed Passion 6.5R | Spur 80 Pinion 24 | Front Tyre Stagger Rib (U6770) | Front Insert N/A | | |
| Ext Gears 35/21 | 33/23 | Differential Height | High <input type="checkbox"/> Low <input checked="" type="checkbox"/> | Rear Topdeck Link | |
| 31/25 | | | | Turnbuckle <input checked="" type="checkbox"/> | Moulding <input type="checkbox"/> |
| Rear Shocks | | Front Shocks | | | |
| Oil Core 550 | Spring Core Blue | Ball Socket | Short <input checked="" type="checkbox"/> | | |
| Piston Holes | 2 <input type="checkbox"/> 3 <input checked="" type="checkbox"/> 4 <input type="checkbox"/> 5 <input type="checkbox"/> 6 <input type="checkbox"/> | Socket | Long <input type="checkbox"/> | | |
| | | | | | |
| Rear Suspension | | | | | |
| Anti roll bar | No <input checked="" type="checkbox"/> | 1.20 <input type="checkbox"/> 1.40 <input type="checkbox"/> 1.60 <input type="checkbox"/> | | | |
| Strap | 3° <input checked="" type="checkbox"/> 4° <input type="checkbox"/> 5° <input type="checkbox"/> | Link Washers 1.0 mm | | | |
| Äntisquat Washers | 1.0 mm | Link Washers x 0 mm | | | |
| Shock Position | Front <input checked="" type="checkbox"/> Rear <input type="checkbox"/> | | | Rear Hub Carrier Alloy <input type="checkbox"/> Std <input checked="" type="checkbox"/> | |
| Wheelbase | Short <input type="checkbox"/> Med <input type="checkbox"/> Long <input checked="" type="checkbox"/> | | | Alloy Hub Carrier +1° <input type="checkbox"/> -1° <input type="checkbox"/> | |
| Rear Camber at Ride Height -2.0 | | | | 49 <input type="checkbox"/> 44 <input type="checkbox"/> 39 <input checked="" type="checkbox"/> 34 <input type="checkbox"/> | |
| Front Suspension | | | | | |
| | | | | | |
| Link Washers 1.0 mm | | | Yoke 0° <input type="checkbox"/> 5° <input checked="" type="checkbox"/> | | |
| Front Camber at Ride Height -1.0 | | | Hub Carrier High <input type="checkbox"/> Low <input checked="" type="checkbox"/> | | |
| Front Toe In +/- 0 | | | 60.0 <input type="checkbox"/> 50.5 <input checked="" type="checkbox"/> 45.5 <input type="checkbox"/> 40.5 <input type="checkbox"/> | | |