

Driver & Event	
Name	Trish
Date	21/09/2017
Event	carpet test
Weather	
Result	

Electrics & Chassis	
E.S.C	Nosram HD
Servo	RSX2 response
Reciever	KO
Batteries	Lipo
Shorty Position	Front <input checked="" type="checkbox"/> Back <input type="checkbox"/>
Transverse Shorty	Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>
Chassis Stiffeners	Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>
Chassis	Alloy <input checked="" type="checkbox"/> Carbon <input type="checkbox"/>

Motor & Gearing	
Motor	5.5
Rotor Diameter	std
Timing	std
Spur	83
Pinion	20

Track Conditions	
Grip Level	High <input checked="" type="checkbox"/> Med <input type="checkbox"/> Low <input type="checkbox"/>
Type	Tight <input type="checkbox"/> Open <input checked="" type="checkbox"/> Mixed <input type="checkbox"/>
Surface	Clay <input type="checkbox"/> Astro <input type="checkbox"/> Grass <input type="checkbox"/> Mixed <input type="checkbox"/> Carpet <input checked="" type="checkbox"/>
Condition	Smooth <input checked="" type="checkbox"/> Bumpy <input type="checkbox"/>

Wheels & Tyres	
Rr Tyre	CACTUS
Rr Wheel	STD WHITE
Rr Insert	U6734
Fr Tyre	CACTUS
Fr Wheel	STD WHITE
Fr Insert	U6733

Notes	
Car weight	g
Wing Gurney Height	mm
Removed middle screws from side pod. U4949 2mm chassis for extra Flex. U4947 2.5 topdecks for Extra Flex. U4944 thickest roll bar 1.3mm U4998 axle high, 2mm WASHERS U7139, Small bore shocks, U4734 U4784, STANDARD PLASTIC REAR HOUSINGS. U3597, U4130, U4789, U4785 u3556, U7002, U4299	

Diff Type	
Diff Oil	
Front	Ball <input type="checkbox"/> Gear <input checked="" type="checkbox"/> 20K
Rear	Ball <input type="checkbox"/> Gear <input checked="" type="checkbox"/> 10K

Front Shocks	
Oil 600	ORANGE
Spring	Shock Cap Sealed <input type="checkbox"/>
	Vented <input type="checkbox"/> Emulsion <input checked="" type="checkbox"/>
Piston White	Drilled <input type="checkbox"/> Hole Size 1.2 mm

Shock Lengthmm

Rear Shocks	
Oil 450	BLUE
Spring	Shock Cap Sealed <input type="checkbox"/>
	Vented <input type="checkbox"/> Emulsion <input checked="" type="checkbox"/>
Piston Black	Drilled <input type="checkbox"/> Hole Size 1.3 mm

Shock Lengthmm

Front Suspension	
Anti roll bar	No <input type="checkbox"/> 1.4 <input checked="" type="checkbox"/> 1.6 <input type="checkbox"/> 1.8 <input type="checkbox"/> 2.0 <input type="checkbox"/>
Camber at Ride Height 1	Deg
Toe-In -1	Deg
Ride Height 16	mm
Washers 2	mm
Track Washers 0	1 mm
Link Washers 4	mm
Front Yoke	7.50 <input checked="" type="checkbox"/> (Kit) 10.0 <input type="checkbox"/>
Hub Spacer	Above <input checked="" type="checkbox"/> Below <input type="checkbox"/>
C.T.R 16	mm

Rear Suspension	
Anti-squat	0° <input type="checkbox"/> 3° <input type="checkbox"/> 1° <input checked="" type="checkbox"/> 4° <input type="checkbox"/> 2° <input type="checkbox"/>
High Pin	Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>
Wheelbase	Short <input type="checkbox"/> Med <input type="checkbox"/> Long <input checked="" type="checkbox"/>
Anti roll bar	No <input type="checkbox"/> 1.0 <input type="checkbox"/> 1.2 <input type="checkbox"/> 1.4 <input type="checkbox"/> 1.6 <input type="checkbox"/> 1.8 <input checked="" type="checkbox"/>
Link Washers 1	mm
Rear Hub Carrier	Alloy <input checked="" type="checkbox"/> Std <input type="checkbox"/>
Alloy Hub Carrier	+1° <input type="checkbox"/> -1° <input type="checkbox"/>
Rear Wishbones	Kit <input type="checkbox"/> Reversed <input type="checkbox"/>
Med Flex	<input type="checkbox"/>
Alloy	Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>
Rear Ride Height 14	mm
Rear Camber at Ride Height -1	Deg
Rear Toe In (Flats IN 2.5°)	<input checked="" type="checkbox"/> (Flats OUT 3.0°) <input type="checkbox"/>
	<input type="checkbox"/> 33.5 (1 Dink) <input checked="" type="checkbox"/> 38.0 (2 Dink) <input type="checkbox"/> 42.5 (3 Dink)

