

Driver & Event	
Name	wesley
Date	2017
Event	national
Weather	indoor
Result	

Electrics & Chassis	
E.S.C	orion
Servo	spektrum
Reciever	
Batteries	
Shorty Position	Front <input checked="" type="checkbox"/> Back <input type="checkbox"/>
Transverse Shorty	Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>
Chassis Stiffeners	Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>
Chassis	Alloy <input checked="" type="checkbox"/> Carbon <input type="checkbox"/>

Motor & Gearing	
Motor	vst orion 5.5
Rotor Diameter	stock
Timing	
Spur	
Pinion	18

Track Conditions	
Grip Level	High <input type="checkbox"/> Med <input checked="" type="checkbox"/> Low <input type="checkbox"/>
Type	Tight <input type="checkbox"/> Open <input type="checkbox"/> Mixed <input checked="" type="checkbox"/>
Surface	Clay <input type="checkbox"/> Astro <input checked="" type="checkbox"/> Grass <input type="checkbox"/> Mixed <input type="checkbox"/> Carpet <input type="checkbox"/>
Condition	Smooth <input checked="" type="checkbox"/> Bumpy <input type="checkbox"/>

Wheels & Tyres	
Rr Tyre	minispike yellow
Rr Wheel	
Rr Insert	medium
Fr Tyre	wide stagger yellow
Fr Wheel	
Fr Insert	medium

Notes	
Car weight	g
Wing Gurney Height	low mm
front rollbar 1mm tried the gear diffs and 7k front and back was good also ball diff had better/safe feeling used allu hub u4998 pin high and inside hole 3mm ring	

Diff Type	
Diff Oil	
Front	Ball <input checked="" type="checkbox"/> Gear <input type="checkbox"/>
Rear	Ball <input checked="" type="checkbox"/> Gear <input type="checkbox"/>

Front Shocks	
Oil	450 red core
Shock Cap	Sealed <input type="checkbox"/> Vented <input type="checkbox"/> Emulsion <input checked="" type="checkbox"/>
Piston	2x1.6 Drilled <input type="checkbox"/> Hole Size mm
Shock Length 22mm	

Rear Shocks	
Oil	450 green core
Shock Cap	Sealed <input type="checkbox"/> Vented <input type="checkbox"/> Emulsion <input checked="" type="checkbox"/>
Piston	2x1.8 Drilled <input checked="" type="checkbox"/> Hole Size mm
Shock Length 27mm	

Front Suspension		Camber at Ride Height 1	Deg	Toe-In 0	Deg
Anti roll bar	No <input type="checkbox"/> 1.4 <input type="checkbox"/> 1.6 <input type="checkbox"/> 1.8 <input type="checkbox"/> 2.0 <input type="checkbox"/>	Ride Height 16	mm	Washers 2	mm
Track Washers 00 mm		Link Washers 2 mm		Front Yoke 7.50 <input checked="" type="checkbox"/> (Kit) 10.0 <input type="checkbox"/>	
C.T.R 16		Hub Spacer Above <input type="checkbox"/> Below <input checked="" type="checkbox"/>			

Rear Suspension		Wheelbase	Short <input checked="" type="checkbox"/> Med <input type="checkbox"/> Long <input type="checkbox"/>
Anti-squat	0° <input type="checkbox"/> 3° <input type="checkbox"/> 1° <input type="checkbox"/> 4° <input type="checkbox"/> 2° <input checked="" type="checkbox"/>	Anti roll bar	No <input type="checkbox"/> 1.0 <input type="checkbox"/> 1.2 <input checked="" type="checkbox"/> 1.4 <input type="checkbox"/> 1.6 <input type="checkbox"/> 1.8 <input type="checkbox"/>
High Pin	Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>	Link Washers 0	mm
Rear Hub Carrier	Alloy <input checked="" type="checkbox"/> Std <input type="checkbox"/>	Alloy	Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>
Alloy Hub Carrier	+1° <input type="checkbox"/> -1° <input type="checkbox"/>		33.5 <input type="checkbox"/> 42.5 <input type="checkbox"/>
Rear Wishbones	Kit <input type="checkbox"/> Reversed <input type="checkbox"/> Med Flex <input checked="" type="checkbox"/>	C/F	
Rear Ride Height 16	mm	33.5 (1 Dink) <input type="checkbox"/>	
Rear Camber at Ride Height 1	Deg	38.0 (2 Dink) <input checked="" type="checkbox"/>	
Rear Toe In (Flats IN 2.5°)	<input type="checkbox"/> (Flats OUT 3.0°) <input checked="" type="checkbox"/>	42.5 (3 Dink) <input type="checkbox"/>	

